

Magellan® 8100

Economical Slim Line Scanner & Scanner/Scale



Features:

- Efficient and ergonomic 360° Scan Volume
- Patented All-Weights™ Platter
- FirstStrike™ Advanced Decoding Software
- Flash Memory for easy upgrades
- Powered auxiliary RS232 port for easy integration of a handheld scanner
- Host diagnostic reporting
- Optional EAS functionality
- 2005 Sunrise Compliant

High Performance Scanning For The Point-Of-Sale (POS)

The Magellan® 8100 scanner and Magellan® 8100 scanner/scale are entry level members of PSC's high-performance Magellan® line for large volume, point-of-sale applications. They feature PSC's patented 360-degree scan pattern for ergonomically correct scanning when seated or standing. In addition, the Magellan 8100 uses the patented All-Weights™ platter for reducing shrink. Select from five different Magellan® 8100 models to fit your particular application and checkstand designs.

Every Magellan® 8100 also includes FirstStrike™, PSC's advanced decoding software for reading torn, poorly printed and disfigured labels of all types. FirstStrike has the ability to autodiscriminate all supported symbologies for added flexibility and features support for Reduced Space Symbology (RSS).

Versatility By Design

The Magellan® 8100 has a powered auxiliary RS232 port for integrating a PSC handheld scanner for those large or heavy items that are often left in the shopping cart. This port can also be used to update the scanner's software in Flash Memory. Additionally, the Magellan® 8100 can be equipped for full electronic article surveillance (EAS) functionality, including Interlock, for one step scanning and security tag deactivation.

Adding even more value to the POS environment, the Magellan® 8100 features host diagnostic reporting software. This software is used to monitor and report the scanner's health to its host. It can prevent scanner downtime by quickly warning management of potential problems before they actually happen.

Easy POS Integration

Since the Magellan® 8100 is from PSC you can count on easy installation and years of worry free operation. The Magellan® 8100 has the same familiar form factor as the Magellan SL® so it installs easily into both new and existing point-of-sale configurations. It also supports industry standard host terminal interfaces, including RS232, IBM 46XX, and IBM USB. In addition, the Magellan® 8100 is compatible with OPOS and JavaPOS systems allowing for even greater integration flexibility at the point-of-sale.

"Nothing Beats a Magellan®"



Specifications

Magellan® 8100

Mechanical

Length & Weight

Model 8100 (short scanner)
13.9" / 35.3 cm & 13.0 lbs. / 5.9 kg
Model 8101 (medium scanner)
15.7" / 39.9 cm & 15.0 lbs. / 6.9 kg
Model 8102 (medium scanner/scale)
15.7" / 39.9 cm & 18.0 lbs. / 8.2 kg
Model 8103 (long scanner)
20.0" / 50.8 cm & 15.0 lbs. / 6.9 kg
Model 8104 (long scanner/scale)
20.0" / 50.8 cm & 20.0 lbs. / 9.1 kg

Width: 11.5" / 29.2 cm

Depth (below counter): 4.0" / 10.2 cm

Height (above counter): 5.1" / 13.0 cm

Scale Capacities

Capacity: 30.0 lbs. / 9.99 kg – 15 kg
(interface dependent)
Minimum increment: 0.01 lb. / 0.005 kg
Vibration immunity: 4 programmable
filter settings
Maximum static weight: 150 lbs. / 68 kg
Adjustments required: Calibration only

Optical

Scan lines: 48
Motor speed: 4500 rpm
Scan rate: 3,600 lines/sec.
Scan zone: 360°
Sides read: 5
Read height: 6.0" / 15.2 cm

Environmental

Temperature rating

Operating: 50° to 104° F / 10° to 40° C

Storage: -40° to 158° F / -40° to 70° C

Humidity: 5 to 95% NC

Electrical

AC Power requirements:

100-250 VAC, 50-60 Hz; 8 Watts (nominal),

12 Watts (maximum), 4 Watts (sleep mode)

Decoding Capability

The Magellan® 8100 autodiscriminates between the following supported symbologies:

UPC Versions A & E

UPC Supplementals (Bookland & Coupon Code)

UPC Add-ons (sub 2 or P2, sub 5 or P5 & C128)

Reduced Space Symbology

(RSS-14, expanded and stacked)

EAN 8, 13

JAN 8, 13

EAN/JAN two label

UCC/EAN 128

Code 39 (with full ASCII)

Code 128

Code 93

12 of 5

Italian Pharmacode

Codabar/NW7

MSI/Plessey

Communications

Host: IBM 46XX, Single & Dual Cable RS232, IBM USB

Other: Powered RS232 auxiliary port; scale host port; remote scale display port; EAS interlock port

Safety / Regulatory

Electrical: AS/NZS 60950 (Australia); CSA-C22.2 No. 60950 (Canada); EN60 950 (TÜV Europe); PSE Mark (Japan); UL 60950 (USA)

Emissions: FCC part 15, Class B (USA); AS/NZS 3548 (Australia/New Zealand); EN 55022-B (Europe); VCCI-B (Japan)

Laser safety: Class IIa Laser Product



(CAUTION: Laser Light – do not stare into beam); IEC 825 Class 1, EN60 825 Class (Europe)

Weights and measures: Australia; Canada; 90/384/EEC (Europe); Mexico; New Zealand; USA (NIST Handbook 44)

Contact your PSC representative for certification schedule and additional listings.

Other

EAS compatibility: Integrated EAS hardware will work with Counterpoint IV, V, VI, and VII models available from Checkpoint® Systems.

Good read acknowledgement with Sensormatic.



PSC Inc.

959 Terry Street
Eugene OR 97402-9150 USA
Tel: 800 695 5700 or 541 683 5700
Fax: 541 345 7140

PSC Worldwide Sales and Service locations

Australia - NSW
Tel: 61 2 9878 8999
Fax: 61 2 9878 8688

Belgium
Tel: 32 2 414 74 09
Fax: 32 2 410 11 63

Brazil
Tel: 55 11 5507 7721
Fax: 55 11 5507 7696

Chile
Tel: 562-339-7000
Fax: 562-339-7985

China
Tel: 86 10 6857 9048
Fax: 86 10 6857 8699

France
Tel: 33 1 64 86 71 00
Fax: 33 1 64 46 72 44

Germany
Tel: 49 6151 93580
Fax: 49 6151 935897

Hong Kong
Tel: 852 25846210
Fax: 852 25210291

India
Tel: 91 11 24621586
Fax: 91 11 24641662

Italy
Tel: 39 039 629031
Fax: 39 039 6859496

Japan
Tel: 81 3 3491 6761
Fax: 81 3 3491 6656

Latin America
Tel: 1 305 539 0111
Fax: 1 305 539 0206

Singapore
Tel: 65 6435 1311
Fax: 65 6226 1242

Spain
Tel: 34 91 746 28 60
Fax: 34 91 742 35 33

Sweden
Tel: 46 4010 84 92
Fax: 46 4010 84 91

United Kingdom
Tel: 44 1923 809500
Fax: 44 1923 809505

Specifications are subject to change without notice.

Additional information concerning this product or other PSC products and services can be found at the PSC website: www.pscnet.com, or contact your PSC representative for more information.

